



RIGHT



FOR STANDING SEAM SPECIFIC MECHANICAL LOAD TEST INFORMATION AND CLAMP INSTALLATION INFORMATION PLEASE VISIT: WWW.S-5.COM

General Notes:

- 1. S-5-H Clamp
- 2. S-5-H Insert
- 3. 3/8-24 Stainless Steel Round Point Setscrew (3/16 Hex Drive)
- 4. M8-1.25 Stainless Steel Hex Flange Bolt (13mm Socket)
- 5. Example roof



MATERIAL: 6061 T6 EST ASSEMBLY WEIGTH	S _® 5!	METAL ROOF INNOVATIONS, LTD. 8655 TABLE BUTTE RD COLORADO SPRINGS, CO 80908 719-495-0518 719-495-0045(FAX)	
O.615 lbs SUPPLIED HARDWARE: M8-1.25 x 16 mm Bolt [2x] 3/8-24 x .800" Setscrews	The Right Way!		
SCALE: 1:1.5	DRAWING NO. H26-A-0-D	DRAWN BY Kati Kadakas	DATE 7/7/2016
EST. WEIGHT: Clamp: 0.4685 lbs Insert: 0.0775 lbs	S-5!® PRODUCTS ARE PROTECTED	D BY MULTIPLE U.S. AND FOREIGN PA	ATENTS.